

T4 Procedure Chair

Common Applications: Surgical, Endoscopy, GI, and Emergency

The T4 can be incorporated across a spectrum of applications and environments. With its universal appeal, it is often utilized as a procedure and/or transport chair, along with serving as a stretcher. When seconds can save lives, you need multi-purpose medical seating solutions.





Transport





Discharge

Our redesigned T4 offers even more clinical and economic advantages to doctors and patients.

From the new sleek color to the new battery to the new triple column base—we've taken a successful procedure chair and made it even better.

- The new battery system eliminates the inconsistencies often found in other battery-operated medical chairs. .
- Powered positioning with memory presets helps eliminate the need for patient transfers and reduce the risk of injuries to patients and staff while improving patient throughput.
- This "one patient, one surface" design contributes to a more spa-like environment, which can soften the harsh aesthetic of traditional surgery centers and create a more comfortable experience for patients.
- The space-saving feature is especially important in alternate site locations. In the seated position, the T4 requires half • the space of a traditional stretcher and is easy to navigate through hallways, elevators, and other close quarters. Plus, the small footprint frees up floor space so additional units can be stored more efficiently.

Details doctors want to know.

- A compact wheelbase and powered height range of 23.5" to 43.5" (59.69 cm 110.49 cm) and 22" to 42" (55.88 cm -106.68 cm on the T4-LB) provides superior surgeon/patient access during procedures.
- The T4, popularly known as the universal care platform, boasts innovative powered patient positioning that helps reduce patient transfers, limiting the risk of injury to patients and caregivers across a variety of healthcare settings.
- Trendelenburg positioning provides efficient functionality and surgical access during procedures.

New Additions!



On-Board Charging Lithium-ion Battery



Memory Presets





The T4 Procedure Chair embodies our One Patient, One Surface[®] philosophy: Each patient remains on one surface throughout their visit—comfort, safety, efficiency, and functionality combined! One piece of equipment also means cost savings, space savings, and time savings. Invest in a procedure chair that puts patients first and affords precise positioning for surgeons, easy access for caregivers, and smoother transport for medical staff.

Admission One Patient, One Surface Procedure

Standard Features

Radiolucent back • Push-button pendant • Central locking brake • Swing & tuck side rails • Electrostatic discharge steering caster

Specifications				
Specifications	T4-XB	T4-B	T4-LB	T4-WB
Wheelbase (length x width)	33" x 20" 83.80 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm	30" x 20" 76.20 cm x 50.80 cm
Weight Capacity	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg	500 lbs. / 226.80 kg
Seat Height (low + high)	23.5" ♦ 43.5" 59.59 cm ♦ 110.49 cm	23.5" ♦ 43.5" 59.60 cm ♦ 110.50 cm	22" ✦ 42" 55.88 cm ✦ 106.68 cm	23.5" ✦ 43.5" 59.59 cm ✦ 110.49 cm
Back Width	24" / 60.96 cm	24" / 60.96 cm	24" / 60.96 cm	28" / 71.12 cm
Side Rail Height (up, seat pan to rail top) + Length	13.5" ★ 27.5" 34.29 cm ★ 69.85 cm	13.5" ◆ 27.5" 34.29 cm ◆ 69.85 cm	13.5" ✦ 27.5" 34.29 cm ✦ 69.85 cm	13.5" ★ 27.5" 34.29 cm ★ 69.85 cm
Overall Chair Height (low + high)	56" ★ 76" 142.24 cm ★ 193.04 cm	56" ✦ 76" 142.24 cm ✦ 193.04 cm	54.5" ★ 74.5" 138.43 cm ★ 189.23 cm	56" ♦ 76" 142.24 cm ♦ 193.04 cm
Seat Width	24" / 60.96 cm	24" / 60.96 cm	24" / 60.96 cm	28" / 71.12 cm
Overall Width (rails up)	31" 78.74 cm	31" 78.74 cm	31" 78.74 cm	35 88.90 cm
Patient Surface Length (standard ★ with optional manual folding footrest)	77" ✦ 71" 195.58 cm ✦ 180.34 cm	77" ♦ 71" 195.58 cm ♦ 180.34 cm	77" ♦ 71" 195.58 cm ♦ 180.34 cm	77" ✦ 71" 195.58 cm ✦ 180.34 cm
Backrest Articulation Range	0° - 90°	0° - 90°	0° - 90°	0° - 90°
Charging System Input Volts	120-240 VAC	120-240 VAC	120-240 VAC	120-240 VAC
Charging System Current	350 mA	350 mA	350 mA	350 mA
Charging System Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Charging System Max Power	38.5 W	38.5 W	38.5 W	38.5 W

Available Accessories

Head Pillow • Lap Belt With Buckle • IV Pole • Oxygen Tank Holder • Arm Board • Side Table With Cushion • Stirrups